

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
24 December 2003 (24.12.2003)

PCT

(10) International Publication Number
WO 03/105745 A1(51) International Patent Classification⁷: A61H 1/02

(21) International Application Number: PCT/GB03/02066

(22) International Filing Date: 14 May 2003 (14.05.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0213693.5 14 June 2002 (14.06.2002) GB

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant and

(72) Inventor: BROADBENT, Hugo [GB/GB]; 41 Fanshaw Road, Eckington, Sheffield S21 4BW (GB).

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

(74) Agent: FRANKS & CO; 9 President Buildings, Savile Street East, Sheffield S4 7UQ (GB).


Published:

— with international search report

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: STRETCHING APPARATUS



(57) **Abstract:** Stretching apparatus for use in stretching the lower limbs of a human subject is disclosed. The apparatus (500) comprises at least one cradle configured to support a leg, or part thereof, of said subject, said cradle moveable between a non-stretching position and a stretching position. At least one cradle movement means (504) is provided operable to move said cradle between said non-stretching and stretching positions. The cradle movement means (504) comprises first movement means configured to move said cradle through a first plane of movement and second movement means configured to rotate said cradle through a second plane of movement transverse to said first plane of movement.